



H40-022-90-120-A

Outdoor IP67 / IK10 Gigabit 95W PoE Switch for Avigilon PTZ / IR PTZ / Multisensor Cameras



AETEK H40-022-90-120-A not only delivers video streaming and 95W PoE budget for Avigilon PTZ, IR PTZ or multisensor camera but also allow these cameras mounted into front panel of H40-022-90-120-A directly. Customized mounting holes on front casing are precisely positioned, absolutely fit the Avigilon pendant wall mount arm kit.

H40-022-90-120-A equipped with 2 of Gigabit PoE ports with 120W power budget and 2 of Gigabit SFP ports, is an all-in-one solution to create a daisy-chain networking for the long-ranged PoE IP surveillance. Robust aluminum casting enclosure endures rated IP67, IK10 and -40°C ~ 65°C (-40°F ~ 149°F) rigid environments.

Features

- Suits pendant wall mount hole of Avigilon PTZ, IR PTZ, and Multi-sensor cameras
- Flexible Gigabit SFP ports for daisy chain network of uplink application
- Casting aluminum enclosure rated IP67 and IK10 impact
- Operating temperature between -40°C and 65°C
- 95W PoE budget for 2 of Gigabit PoE ports
- Supporting 10/100/1000Mbps data rates
- 12KV PoE & 10KV AC surge protections
- Field test working with Avigilon bt PoE Camera

Applications

AETEK H40-022-90-120-A with Avigilon H4 Multisensor :



AETEK H40-022-90-120-A with Avigilon H4 IR PTZ :



Applications

AETEK H40-022-90-120-A with Avigilon H5A PTZ :



Specifications

	H40-022-90-120-A
Networking Specifications	
Total Gigabit Ports	4
Gigabit PoE Port (10M/100M/1G)	2x95W PoH PoE
Gigabit SFP Slots	2
Forwarding Capacity	11.904Mpps
Mac Table	8k
Jumbo Frames	9,216 Bytes
Switching Capacity	8 Gbps
Power Specifications	
Input Voltage	100VAC ~ 240VAC 280VAC 4hr 300VAC 1min.
Backup Power Input Voltage	48-56VDC
Output Voltage Range / port 1~port 2	54 VDC PoE IEEE 802.3af (Max. 15.4W) output PoE+ IEEE802.3at (Max. 30W) output PoH PoE (Max.60W/95W) output
Power Budget	120W
Surge Protection /each PoE Port	12KV
Surge Protection for AC power	10KV
Mechanical Specifications	
Dimensions (L x W x H)	255.2 x 199.8 x 95 mm
Weight	3.2 kg (7.05 lb)
Connectors	M25 x 2
Environmental Specifications	
Weather Rating	IP67
Vandal Proof	IK10
Operating Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Operating Humidity	5% ~ 95% non-condensing
Certifications	
EMC	CE, FCC, VCCI, C-Tick Class A
Safety	EN62368-1
Surge	EN61000-4-5

Optional Accessories

SFP Modules



SFP-ISX-X5

Industrial Gigabit SFP Transceiver

- MMF
- 0.5 km
- -40°C ~85°C



SFP-ISX-02

Industrial Gigabit SFP Transceiver

- MMF
- 2 km
- -40°C ~85°C



SFP-ILX-10

Industrial Gigabit SFP Transceiver

- SMF
- 10 km
- -40°C ~85°C



SFP-ILX-40

Industrial Gigabit SFP Transceiver

- SMF
- 40 km
- -40°C ~85°C



SFP-ITX-X1

Industrial Gigabit SFP Transceiver

- SFP
- 100 km
- -40°C ~85°C

Pole Mount Brackets



AT-100

Pole Mount Adapter



AT-101

Pole Mount Adapter

Corner Mount Bracket



AT-200

Corner Mount Adapter