



# ARD-AYK12 - RFID Proximity reader



- ▶ Reader with beeper and multicolored LED display
- ▶ Wiegand output for EM
- ▶ Indoor and outdoor mounting

## Certifications and Approvals

USA: UL 294 & FCC Part 15B

Europe: CE

## Installation/Configuration Notes

The ARD-AYK12 is supplied with an 18 inch (45 cm) pigtail. The table below shows how to wire the reader to the controller.

COLOR	WIEGAND OUTPUT
Red	DC + Input
Black	Ground
White	Data 1
Green	Data 0
Brown	LED Control
Purple	Tamper

**Note** When using a separate power supply for the reader, this supply and the cable shield wire on the reader should be attached to an earth ground (best) or signal ground connection at the panel or power supply end of the cable.

## Technical Specifications

### Electrical Characteristics

Power supply type	Linear type recommended
Operating voltage range	5 – 16 VDC
Maximum input current	Standby: 35 mA Read: 50 mA
Tamper output	Open collector, active low, max. sink current 16 mA
RF modulation	ASK

### Ranges

Max. cable distance to controller	500 ft. (150 m)
Operating temperature range	-25°F to 145 °F (-31 °C to 63 °C)
Operating humidity	0 to 95% (non condensing)
Read range*	3.15 inch (8 cm)
Dimensions (H x W x D)	3.15 x 1.57 x 0.50 inch (80 x 40 x 13 mm)

\* The reading range depends on card type, electrical environment, and/or proximity to metal.

**Ordering Information**

**ARD-AYK12 - RFID Proximity reader**      **ARD-AYK12**  
Access control card reader with Wiegand output for 125 kHz card technology (EM).

**Accessories**

**ACD-ATR11ISO - RFID Card**      **ACD-ATR11ISO**  
Standard 125 kHz proximity read-only card for Wiegand readers type W 3.

**ACD-ATR14CS - RFID Card**      **ACD-ATR14CS**  
Clamshell standard 125 kHz proximity read-only card for Wiegand readers type W 3.

**ACA-ATR13 - RFID Tag**      **ACA-ATR13**  
125 kHz proximity read-only tag for Wiegand readers type W 3.

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**