

DS-6908UDI(B) Decoder



- Provides HDMI (adaptable to DVI-D) and BNC output interfaces.
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for odd interface).
- H.265+/H.265, H.264+/H.264, Hik264, MPEG4 and MJPEG video compression.
- PS, RTP, TS, ES, HIK encapsulation formats.
- Three encoding levels: baseline, main, and high-profile.
- G.722, G711A, G726, G711U, MPEG2-L2, and AAC audio compression.
- Two decoding modes: active decoding and passive decoding.
- Remote video files' decoding output.
- Supports two-way audio via client software.
- Provides VGA and DVI input interfaces.
- Supports window opening, window roaming and window split.
- Supports multi-screen control with PC installed with RSC server.
- Gets stream and decodes via URL and RTSP from encoding devices.
- Displays the decoded video stream on the video wall by directly linking cameras or by stream media forwarding.
- You can configure what the video wall shows when decoding ends and streaming fails via the Web browser and client software.
- Configurable LED width and height parameters when the LED is connected.
- Regular and irregular virtual screen configurable to display multiple signal sources and get rid of the restriction of physical screen.
- Accessible by 2.4 MP DeepinView camera.
- Accessible by thermal network camera and you can view the temperature measurement, dynamic fire source detection, ship detection and VCA information in live view and playback.
- You can enable or disable the smart information for the thermal network camera.
- Two-way audio.
- Port aggregation technology (Ethernet Channel).



▪ Specification

| Model | | DS-6908UDI(B) |
|--------------|-----------------------|---|
| Input/Output | Input | VGA, DVI-I |
| | Input Resolution | VGA, DVI-I: 1080p: 1920 × 1080@50/60 Hz, 720p: 1280 × 720@50 Hz/60 Hz |
| | Output | HDMI × 8, BNC × 4 (DB15 × 1) |
| | Output Resolution | HDMI: 4K: 3840 × 2160@30 Hz (for odd interface only) , 1080p: 1920 × 1080@50/60 Hz, 720p: 1280 × 720@50 Hz/60 Hz BNC: PAL: 704 × 576, NTSC: 704 × 480 |
| Decoding | Decoding Resolution | Up to 24MP (only for 3 encoder tracks mode) |
| | Decoding Channel | 64-ch |
| | Decoding Capability | 24MP@30fps: 4-ch, 12MP@20fps:8-ch, 8MP@30fps: 16-ch, 5MP@30fps: 24-ch, 3MP@30fps: 40-ch, 1080p@30fps: 64-ch |
| | Split Screen | 1/4/6/8/9/12/16/25/36 |
| Interface | Network Interface | RJ45 interface × 2, 10/100/1000 Mbps adaptive Optic interface × 2, 100 base-FX/1000 base-X An RJ45 interface and an optic interface form a combo. |
| | Serial Interface | RS-232 (RJ45) × 1, RS-485 × 1 |
| | Two-way Audio Out | 1 (3.5 mm connector, 2.0 Vp-p, 1 KΩ) |
| | Two-way Audio In | 1 (3.5 mm connector, 2.0 Vp-p, 1 KΩ) |
| | Alarm In | 8 |
| | Audio Output | 8 (DB15 × 1) |
| | Alarm Out | 8 |
| General | Power Supply | 100 to 240 VAC |
| | Power Consumption | ≤ 70 W |
| | Working Humidity | 10% to 90% |
| | Working Temperature | -10 °C to 55 °C (14 °F to 131 °F) |
| | Dimensions(W × D × H) | 440 mm × 320.8 mm × 44.5 mm (17.32 inch × 12.63 inch × 1.75 inch) |
| | Weight | ≤ 5.20 kg (11.46 lb) |

▪ Available Model


DS-6908UDI(B)

Physical Interface




| Front Panel | Description | Rear Panel | Description |
|-------------|--|--------------------|---|
| VGA IN | VGA input indicator | AUDIO OUT | Audio output interface |
| DVI IN | DVI input indicator | VIDEO OUT | Video output interface |
| POWER | Power indicator | HDMI OUT | HDMI video output interface |
| G1 | 10/100/1000 Mbps Ethernet interface 1 | VGA VIDEO IN | VGA video input interface |
| G2 | 10/100/1000 Mbps Ethernet interface 2 | DVI VIDEO IN | DVI video input interface |
| OPT1 | 10/100/1000 Mbps optical interface 1 | LINE IN/OUT | Line input/output interface |
| OPT2 | 10/100/1000 Mbps optical interface 2 | ALARM IN/ALARM OUT | RS-485 interface, alarm in and output interface |
| RS-232 | Connect to RS-232 devices, e.g., PC etc. | - | - |
| USB | USB 2.0 interface | - | - |

Dimension



Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
Info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7852-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-97-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com