



KTS S.r.l.
Via Madonna delle Grazie, 53
80018 Mugnano di Napoli
Tel: +39 081 5713050
commerciale@ktsables.com



ALARM CABLE HF2P-C LSZH Cca s1a,d0,a1

TECNICAL FEATURES

CONDUCTORS

Flexible red copper

INSULATION

LSZH M1 (Low smoke emission)

ASSEMBLY

conductors stranded in layers

SCREEN

Alluminium/Polyester tape

Drain wire flexible red copper


JACKET

LSZH M1 (Low smoke emission) White

PACKAGING AVAILABLE

Coil 200 mt.

Spool 500 mt.



200m



500m

MARKING

KTS s.r.l. ALARM CABLE (cod.) (sez.) EUROCLASS CPR Cca s1a-d0-a1 2019

IEC 60332-3-25 UNEL 36762 C4 U/o 400 V MT. BATCH CE MADE IN ITALY

Table n° 001

ELECTRICAL FEATURES

TEST VOLTAGE

1000 V

INSULATION RESISTANCE

> 200 MΩ/Km

TEMPERATURE RANGE

-10°/ +70°

BENDING RADIUS

10 X Ø

STANDARDS

Insulation and sheath

CEI EN 50363

Flame retardant

IEC 60332-1-2

Fire retardant

IEC 60332-3-25

Low smoke emission

CEI EN 50267-2-3

coexistence with cables CAT. 1

UNEL 36762

European directive Rohs 2011/65/EU

CPR REACTION CLASS

Harmonized standard

EN 50575:2014 + A1:2016

Reaction to fire

Cca s1a,d0,a1

Hazardous substance

Nothing

Marking:



PRODUCTS:

| Code | Nominal Section | Outer dia. +/- 0,2mm | Packaging | Copper | | Cond. Resistance Ohm/Km | Jacket colour |
|------------|--|-------------------------|---------------------|---------|--------|----------------------------|------------------|
| | | | | 24x0.20 | 7x0.17 | | |
| 2K22SHF-C | ALARM CABLE ALHF-C SCH. Cca - 2x0.75+2X2X0.22 | 5,50 | M100 - M200 - B500* | 24x0.20 | 7x0.17 | 26/108 | WHITE |
| 2K22S2HF-C | ALARM CABLE ALHF-C SCH. Cca - 2x0.75+2X2X0.22+2X0.22 | 6,00 | M100 - M200 - B500* | 24x0.20 | 7x0.17 | 26/108 | WHITE |
| 2K22S6HF-C | ALARM CABLE ALHF-C SCH. Cca - 2x0.75+2X2X0.22+6X0.22 | 7,00 | M100 - M200 - B500* | 24x0.20 | 7x0.17 | 26/108 | WHITE |